



## LEERING MISTRAL® JUNIOR

CHF 6'513.40

**Sandblast efficiently and quickly**  
**Trouble-free sandblasting process**  
**Permanent good visibility thanks to good air circulation and dust removal**  
**Solid construction and dust seals**

### Technical specifications

|                  |                                                          |
|------------------|----------------------------------------------------------|
| Outside cabin:   | 1250 mm x 1280 mm x 1925 mm (W x D x H)                  |
| Inside cabin:    | 1100 mm x 800 mm x 870 mm (W x D x H)                    |
| Door openings:   | 690 mm x 795 mm (W x H)                                  |
| Weight:          | approx. 275kg                                            |
| Air consumption: | 800-1'000 liters / min. at 4 bar and Ø 8 mm sand nozzle. |

---

## PRODUCT DESCRIPTION

**Mistral®** blasting cabins can be delivered directly from stock at a very attractive price. The **Mistral® Junior** blasting cabin works on the injector principle. With **Mistral® Junior** you achieve an excellent blasting result - and at a very reasonable price.

### Technical specifications

|                  |                                                          |
|------------------|----------------------------------------------------------|
| Outside cabin:   | 1250 mm x 1280 mm x 1925 mm (W x D x H)                  |
| Inside cabin:    | 1100 mm x 800 mm x 870 mm (W x D x H)                    |
| Door openings:   | 690 mm x 795 mm (W x H)                                  |
| Weight:          | approx. 275 kg                                           |
| Air consumption: | 800-1'000 liters / min. at 4 bar and Ø 8 mm sand nozzle. |

### Equipment

- Profile-reinforced cabin made of strong sheet steel.
- 2 swing doors with pneumatic safety devices.
- LED unit 20 W, covered with tempered glass.
- Tempered safety glass at the front, with baffle plate, quick release.
- Work grate made of perforated sheet metal (3 mm thick).

**Dedusting and dust separation system**

- 1 filter cartridge 4 m<sup>2</sup> filter area (dust discharge <1.8 mg / m<sup>3</sup>).
- 1 solenoid valve with electronic control for automatic cleaning.
- 1 Fan motor 0.55 kW.
- Electrical equipment: 230 V / 50 Hz
- Operation manual
- Spare part list.

**Color: RAL 7001 textured paint.**